
 Please refer to the description of the Control Centre / Control to identify the manual call points that can be connected.

1 Manual call point RT 2

- Manual call point to VdS 2592 for the connection to SHEVS Control Centres / Controls
- Orange design with VdS approval
- Inscription “RAUCHABZUG” (smoke exhaust)
- Indicator alarm 
- 0,9 mm thin break glass to DIN 1249
- Environmental conditions: -10 °C ... +55 °C, 20 % ... 80 % rel. humidity (non condensing)
- Lockable ABS housing
- Dimensions in mm (W x H x D): 125 x 125 x 35
- Protection rating IP42
- Each unit comes with a key
- Also available with customised inscriptions

Standard - Versions

Series RT 2-K-* (secondary alarm point)

RT 2-K-OR: Version in orange, VdS approved

RT 2-K-BL: Version in blue

RT 2-K-RT: Version in red



RT 2-K-GR: Version in grey

RT 2-K-GE: Version in yellow



Series RT 2-K-*-BS (main alarm point)

Same as secondary alarm point, but additionally

- Indicators operation  and malfunction 
- Internal button to reset the alarm

RT 2-K-OR-BS: Version in orange, VdS approved

RT 2-K-BL-BS: Version in blue

RT 2-K-RT-BS: Version in red


RT 2-K-GR-BS: Version in grey

RT 2-K-GE-BS: Version in yellow



Series RT 2-K-*-BS-A (main alarm point with indication of position)

Same as main alarm point, but additionally

- Indication of position OPEN 

RT 2-K-OR-BS-A: Version in orange, VdS approved

RT 2-K-BL-BS-A: Version in blue

RT 2-K-RT-BS-A: Version in red

RT 2-K-GR-BS-A: Version in grey

RT 2-K-GE-BS-A: Version in yellow



Aluminium versions

- Same as standard version, but aluminium housing with protection rating IP 43



Series RT 2-A-* (secondary alarm point)

RT 2-A-OR: Version in orange, VdS approved
RT 2-A-BL: Version in blue
RT 2-A-RT: Version in red
RT 2-A-GR: Version in grey
RT 2-A-GE: Version in yellow



Series RT 2-A-*-BS (main alarm point)

Same as secondary alarm point, but additionally


- Indicators operation  and malfunction 
- Internal button to reset the alarm

RT 2-A-OR-BS: Version in orange, VdS approved
RT 2-A-BL-BS: Version in blue
RT 2-A-RT-BS: Version in red
RT 2-A-GR-BS: Version in grey
RT 2-A-GE-BS: Version in yellow



Series RT 2-A-*-BS-A (main alarm point with indication of position)

Same as main alarm point, but additionally

- Indication of position OPEN 

RT 2-A-OR-BS-A: Version in orange, VdS approved
RT 2-A-BL-BS-A: Version in blue
RT 2-A-RT-BS-A: Version in red
RT 2-A-GR-BS-A: Version in grey
RT 2-A-GE-BS-A: Version in yellow



Options




AA:

- Internal mini-buzzer for indication of alarm and malfunction
- Internal button to reset the mini-buzzer
- Available for main alarm points only

IP54:

- Set for weather protection and sealing, increases protection rating to IP54
- For aluminium versions only

2 Manual call point RT 3

- Manual call point to VdS 2592 for the connection to SHEVS Control Centre type **RWZ 2f**
- Inscription "RAUCHABZUG" (smoke exhaust)
- Indicators operation , alarm  and malfunction 
- Internal button to reset the alarm
- 0,9 mm thin break glass to DIN 1249
- Environmental conditions: -10 °C ... +55 °C, 20 % ... 80 % rel. humidity (non condensing)
- Lockable ABS housing
- Dimensions in mm (W x H x D): 125 x 125 x 35
- Protection rating IP42
- Each unit comes with a key
- Also available with customised inscriptions

Series RT 3-K-*-BS (main alarm point)

RT 3-K-OR-BS: Version in orange



3 Manual call point RT-230

- Manual call point to DIN 14655
- Inscription "RAUCHABZUG" (smoke exhaust)
- Internal lever to reset the alarm
- 0,9 mm thin break glass to DIN 1249
- 1 change-over contact, contact load rating 230 V~ / 1 A
- For direct connection to 230 V Systems (not suitable for 24 V SHEVS Control Centres)
- Terminals for cables up to 1,5 mm²
- Environmental conditions: -10 °C ... +55 °C, 20 % ... 80 % rel. humidity (non condensing)
- Lockable aluminium housing
- Dimensions in mm (W x H x D): 125 x 125 x 35
- Protection rating IP43
- Each unit comes with a key
- Also available with customised inscriptions

Series RT-A-*-230

RT-A-OR-230: Version in orange

RT-A-BL-230: Version in blue

RT-A-RT-230: Version in red

RT-A-GR-230: Version in grey

RT-A-GE-230: Version in yellow



Option


IP54:

- Set for weather protection and sealing, increases protection rating to IP54

4 Accessories

RT-E

- Spare glass sheet, blank, for manual call points series **RT** *
- 0,9 mm thin break glass to DIN 1249
- Dimensions in mm (W x H): 80 x 80
- 1 packing unit = 10 pieces



RT-E:

RT-S

- Spare key for manual call points series **RT** *

RT-S-K: Standard key



RT-S-A: Metal key

